



**Professional Solutions - Unrivalled Value**

Double universal adjustable height ceiling mount for 37" to 63" flat panel screens, ideal for commercial or retail settings. Continuous tilt of 20° forward with locking knob and 360° rotation for perfect screen positioning. Makes a secure installation quick and easy, simply hang the screens and turn the pre-assembled securing screws to lock in place. Compatible with all 1.5" NPT threaded pipe.

37"- 63" / 94cm-160cm

200 LB / 91 KG

■ **Various Screen Sizes**

Fits most 37" to 63" flat panel screens weighing 200lb or less.

■ **Multi-angle Positioning**

Up to 20° of continuous tilt and 360° rotation.

■ **Easy Installation**

Pre-assembled securing screw makes installation fast and easy.

■ **Standard Fixed Extension**

Standard drop lengths available in 18" and 3' lengths.

■ **Cable Management**

Easily route cables through 1.5" diameter extension column.

■ **Universal Design**

Works with any hole pattern up to 723mm (28.5") x 501mm (19.8") in height.

■ **Included Hardware**

Pre-sorted hardware pack for easy component selection and installation (hardware for installation to wood studs or concrete surfaces included).

**Functional Specifications**

Tilt: +20°/-0°

Rotation: 360°

**Mounting Surfaces:** Structural wood beams (with included hardware) & concrete & other structural surfaces (requires additional hardware or accessories).

**MaxMountingPattern:**

723mm(28.5") width  
501mm (19.8") height

**Load Capacity:** 200 LB / 91 KG

**Drop Length:** 18"  
**Warranty:** Limited 10 Years

**Universal Design**  
Works with any hole pattern up to 723mm (28.5") x 501mm (19.8") in height.

**Mounting Surface**  
Standard 1.5" NPT threaded connection.

**Tilt**  
0 to +20° tilt for optimal viewing angles.

**Pre-Installed Securing Screws**  
Easy hook and secure installation and pre-assembled securing screw makes installation fast and easy.

**Lateral Adjustment**  
Lateral adjustment functionality for positioning TV in the right spot on the wall.




**Mounting Hardware**  
Complete set of screen mounting hardware, labeled for ease of use and ready to go.



# Single Flat Panel Ceiling Mount

For 37" to 63" (94-160cm) LCD and Plasma TV's

C63-18 (BLACK)




## Product Specifications

## Package Specifications

PRODUCT WEIGHT	LOAD CAPACITY	COLORS	FINISH	PACKAGE SIZE (WxHxD)	SHIP WEIGHT	UPC CODE	PACKAGE CONTENTS
20 lb (9 kg)	200lb (91 Kg)	Black	Scratch resistant powdercoating	39" x 12" x 9" (996x300x224mm)	25.6 lb (11.6Kg)	C63-18 (Black)	Mount, screen mounting hardware, product manual.

## Mounting Interface



	Universal		VESA										
	Min	Max	W 75mm	W 100mm	W 200mm	W 200mm	W 300mm	W 300mm	W 400mm	W 400mm	W 400mm	W 600mm	W 600mm
W	31mm	723mm	X	X	X	X	X	X	X	X	X	X	X
H	31mm	501mm	H 75mm	H 100mm	H 100mm	H 200mm	H 200mm	H 300mm	H 200mm	H 300mm	H 400mm	H 200mm	H 400mm

## Accessories

### Suspended Ceiling Adapters



CAS1W

For mounting above a false ceiling tile. 13" of lateral shift for fast project adjustment. Compatible with all 1.5" NPT threaded pipe.



CAS2W

Replaces a standard 2' x 2' grid. 13" of lateral shift for fast project adjustment. Compatible with all 1.5" NPT threaded pipe.

### Structural Ceiling Adapters



CA1

Wood Single Joist / Concrete



CA2

Wood 16" Double Joist / Concrete



CA4

General Purpose 4x4"



CA8

General Purpose 8x8"

### Truss Ceiling Adapter



CAT3

Mounts to round, square and rectangular trusses from .75" up to 3" in diameter and is compatible with all 1.5" NPT threaded pipe.

### Vaulted Ceiling Adapter



CAV1

For installation on cathedral or vaulted ceilings. Adjusts up to 94° and is compatible with all 1.5" NPT threaded pipe.

### Unistrut Ceiling Adapters



CAU1

Bracket and hardware for mounting to single 1-5/8"x1-5/8" Unistrut.



CAU4


Bracket and hardware (4x4) for mounting to standard 1-5/8"x1-5/8" dual channels spaced on 2.25" centers.



CAU8

Bracket and hardware (8x8) for mounting to standard 1-5/8"x1-5/8" dual channels spaced on 6" centers.

### Unistrut Bolts



HU2 (2 Bolts) HU4 (4 Bolts)

3/8" bolts and spring nuts for mounting ceiling brackets to standard 1-5/8"x1-5/8".

### Fixed Columns

Static ceiling columns for use with all ceiling adapters using standard 1.5" NPT interfaces. Connectors (sold separately) give ability to extend drop lengths by connecting two or more columns. Cable management with a completely open interior.



BLACK	DROP
E06	6"
E1	12"
E018	18"
E2	2'
E3	3'
E4	4'
E5	5'
E6	6'
E7	7'
E8	8'
E9	9'
E10	10'

### Adjustable Columns

Adjustable extension columns designed for use with all ceiling adapters using standard 1.5" NPT interfaces. Column allows for flexibility with quick 1" incremental drop length adjustments and cable management with a completely open interior. Connectors (sold separately) give ability to extend drop lengths by connecting two or more columns.



BLACK	DROP
EA0611	6"-11"
EA01218	12"-18"
EA01824	18"-24"
EA23	2'-3'
EA24	2'-4'
EA35	3'-5'
EA46	4'-6'
EA57	5'-7'
EA68	6'-8'
EA79	7'-9'
EA810	8'-10'
EA911	9'-11'
EA1012	10'-12'

Visit [crimsonav.com](http://crimsonav.com) to see the full line of vidamounts LCD/plasma, projector and TV/monitor mounts. © 2010 Crimson AV LLC. All rights reserved.